

### Food Contact Plastics

## Certificate of Conformity with the Requirements of EU Regulation 10/2011, as amended by EU Regulations 321/2011, 1282/2011, 1183/2012, 202/2014, 174/2015, 1416/2016, 752/2017, 79/2018, 213/2018 and 831/2018.

**Certificate no: 2012/4668B**

**Product name:** HDPE Resin; 'HD 3840 UA'  
**Manufacturer:** Sidi Kerir Petrochemicals Co. "SIDPEC"  
**Address:** km 36 Alex-Cairo Desert Road, Alnahda, Alameria, Alexandria, EGYPT  
**Date of Issue:** 7 February 2012  
**Reviewed:** 8 November 2018  
**SMP Ref no:** 07A12J3146/11A12J4763/16A12J6422

Samples manufactured from the above resin have been tested for overall migration with the simulants and test conditions listed below.

Food Simulants	Test Conditions		
	Duration	Temp/°C	Test
Simulant A, B and D2	10 days	40°C	TI

TI = exposure to food simulant by total immersion.

The overall migration results obtained were found to be below the overall migration limits defined in EU Regulation 10/2011.

Additionally, Smithers Pira have carried out an audit of the formulation of the above product. All monomers and additives contained in the formulation are approved for use in food contact plastics and are listed in Annex I of EU Regulation 10/2011. The following substance(s) are subject to restrictions under this legislation;

- Poly[6-[(1,1,3,3-tetramethylbutyl)amino]-1,3,5-triazine-2,4-diyl]-[(2,2,6,6-tetramethyl-4-piperidyl)-imino] hexamethylene[(2,2,6,6-tetramethyl-4-piperidyl) imino], PM Ref 81200, CAS 71878-19-8, FCM No 740, SML = 3 mg/kg
- Zinc salt of stearic acid, PM Ref 89040, CAS 57-11-4, FCM No 106, SML = 5 mg/kg (as Zn)
- Reaction product of di-tert-butylphosphonite with biphenyl, obtained by condensation of 2,4-di-tert-butylphenol with Friedel Craft reaction product of phosphorous trichloride and biphenyl, PM Ref 83595, CAS 119345-01-6, FCM No 760, SML = 18 mg/kg

Experimental studies and/or migration modelling using an accepted EU model (Migratest Lite) with exposure condition of 10 days at 50°C, a material thickness of 500 µm and the conventional EU ratio of 6 dm<sup>2</sup> of packaging per kg of food have shown that the above restriction/s will not be exceeded under these conditions.

The formulation of the above resin contains no multiple function additive/s; (NB Multiple function additives are defined as those which are also approved for direct addition into foods and which would therefore be subject to separate food regulations).

**The above resin can therefore be used to manufacture products which meet the requirements of EU Regulation 10/2011, as currently amended, for use with all classes of foodstuff for;**

- any long term storage (for periods less than 6 months) at room temperature or below, including when packaged under hot-fill conditions, and/or
- heating up to a temperature T where 70 °C ≤ T ≤ 100 °C for a maximum of  $t = 120/2^{((T-70)/10)}$  minutes.

The product therefore also meets the safety requirements laid out in Article III of EC Regulation 1935(2004) under the above conditions of use.

NB Users are reminded that EU Regulation 10/2011 relates to finished articles/materials manufactured from plastics. Users of the above products are responsible for ensuring that their finished products comply with the overall migration limit and any specific migration limit/s mentioned above, by conducting appropriate tests on their finished products.

Certified by: **Dr Alistair Irvine**   
**Manager, Food Contact Compliance**